

Utilux Lugs Nomenclature

E.g.

BG

Description

X

Description

4

HR

Sector lugs only

240

Conductor Area

M12

Stud Size

/1

Pack Size

AG = Aluminium Lug
 BG = Bimetal Lug
 CG = Copper Lug
 CGNP = Copper Lug Narrow Palm
 CG**FL = Copper Lug FLared
 CG**SD = Copper Lug Solid Palm
 SEG = Copper SEaled Lug
 BGRV = Bimetal Lug Reverse

X = Generic
 Parts Used in Custom Connectors
 3 = 3 Core Sector
 S = 3 Core Sector
 4 = 4 Core Sector

I = Indent crimp
 H = Hex Crimp
 HR = Hex Crimp with rotating core

Conductor Area mm Sq
 LP = Long Palm
 MB = Blank Palm

e.g.: /25 = PPQ =1
Note if no /number = PPQ of 1

Note * = conductor Range

Utilux Links/Stalks Nomenclature

E.g.

BK

Description

X

Description

3

I

Sector lugs only

240

Conductor Area

- 185

Conductor Area

/1

Pack Size

AK = Aluminium Link
 BK = Bimetal Link
 BS = Bimetal Stalk
 CS = Copper Stalk
 CK = Copper Crimp Links
 AKR = Aluminium Link Reducing
 BKR = Bimetal Link (UCC Range)
 CKR = Copper Link Reducing
 CKB = Copper Crimp Links With Solid Barrier

X = Generic
 Parts Used in Custom Connectors
 3 = 3 Core Sector
 S = 3 Core Sector
 4 = 4 Core Sector

I = Indent crimp
 H = Hex Crimp
 HR = Hex Crimp with rotating core

= Large End or sector size
 = Small End or Stalk size. Not required if link is same size both ends

e.g.: /25 = PPQ = 1
Note if no /number = PPQ of 1